

STRUCTURAL ENGINEERING



QUARTERLY JOURNAL OF
INDIAN SOCIETY
OF
STRUCTURAL ENGINEERS

ISSE

VOLUME 12-4

Oct-Nov-Dec-2010



**OUTSTANDING
STRUCTURAL ENGINEER
ISAMBARD KINGDOM
BRUNEL**

(See page 12 inside)



LET US BUILD A STRONG STRUCTURE OF INDIAN SOCIETY



ArcelorMittal

Complete & Customized Foundation Solutions



Unique project where sheet piles are used in India (to name a few):

- Quay Wall for Port Construction - Vaizag Port Trust
- Drydock Project - Bhavnagar Drydock
- Underground Car Park - Kolkata Car Park Project
- Hydro Power Projects - BASPA Hydro Project
- Thermal Power Project - Farakka Power Project
- Desalination Project - Chennai Desalination Project
- Under pass Construction - At Cochin, Kerala Project
- Flood Control Project - Assam Irrigation Project

Various sections available:

- Z Sheet Piles
- U Sheet Piles
- Straight Web Sections
- Box Piles
- Combined Walls (HZ / Tubular Piles)

Distribution Solutions India - one stop shop: steel solutions & services

Sheet piles: now readily available in India, at our stockyard

ArcelorMittal Distribution Solutions India Pvt. Ltd.

Mumbai Office T 09 920 160 019 | Kolkata Office T 09 239 417 632

Delhi Office T 09 920 160 019 | Chennai Office T 09 007 006 800

E amdsindia@arcelormittal.com | www.arcelormittal.com/projects

STRUCTURAL ENGINEERING

QUARTERLY JOURNAL OF

INDIAN SOCIETY

OF

STRUCTURAL ENGINEERS

VOLUME 12-4, OCT-NOV-DEC 2010



ISSE

Head Office : C/O. S G Dharmadhikari, 24, Pandit Nivas, 3rd Floor, S K Bole Marg
Dadar (W), Mumbai - 400 028 • Tel. 91-22 24365240 • Fax . 91-22 -2422 4096

• E-mail : issemumbai@gmail.com • Website : www.isse.org.in

Regd. Office : The Maharashtra Executor & Trustee Co. Ltd., Bank of Maharashtra, Gadkari Chowk
Gokhale Road (N), Dadar, Mumbai - 400 028

Charity Commissioner Reg. No. E 17940, Mumbai Donations are exempted from Income Tax under 80-G

FOUNDER PRESIDENT :

Late Eng. R L Nene

Contents

Parent Advisors:

..... M C Bhide
..... M D Mulay
..... S G Patil

ISSE WORKING COMMITTEE :

President S G Dharmadhikari
Secretary K L Savla
Treasurer M M Nandgaonkar
Members P B Dandekar
..... M V Sant
..... J R Raval
..... D S Joshi
..... U V Dhargalkar
..... S H Jain
..... H S Vadalkar
..... G B Chaudhari
..... N K Bhattacharyya

ISSE - PUNE CENTRE

Chairman Surendar Suchdeo
Secretary Upendra Purandare
Jt. Secretary Kedar Phadnis
Treasurer Dhananjay Hirwe

ISSE - SOLAPUR CENTRE

Chairman Sunilkumar Patil
Secretary Om Darak
Jt. Secretary Jagdish Diddi
Treasurer Vaibhav Homkar

ISSE - MUMBAI CENTRE

Chairman Kamal Hadker
Secretary Shekhar Ghate
Treasurer H. M. Raje

❖ Fraternity News	2
❖ Elevated Viaduct for Delhi Metro Rail Corporation in Dwarka Sub city By Rajan Kataria, Haroon Shaikh and V. V. Nori	3
❖ Jack-up Platform for Marine Works By A B Karnik	8
❖ Outstanding Structural Engineer Isambard Kingdom Brunel By Dr. B N Kale	12
❖ Inbuilt Ferrocement Structural Formwork By J A Desai	18
❖ Missing You !	22

Editor : N K Bhattacharyya

Jt. Editor : Hemant Vadalkar

Views expressed are authors' or reporters' personal and do not necessarily reflect views of ISSE. ISSE is not responsible for any consequent actions based on contents or information given in the journal.

Fraternity News

WELCOME TO NEW MEMBERS

(Oct-Dec 2010)

LIFE MEMBERS

M-1049 Kiran Keshav Bhavsar

M-1051 Chandrashekhar Shripad Keskar

M-1053 Kishor Balasaheb Kelgandre

M-1050 Ashok Ramai Gupta

M-1052 Santha Rao Pachala

M-1054 Anand Purshottam Agrawal

ORGANISATION MEMBER

OM-15 Soft Tech Engineers (P) Ltd.

OM-16 Outokumpu India Pvt. Ltd.

REVISED STRENGTH AS ON 31-12-2010

Patrons : 29

Organisation Members : 16

Sponsors : 8

Members : 1054

Junior Members : 9

TOTAL STRENGTH : 1116

AIMS & OBJECTIVES

1. To restore the desired status to the Structural Engineer in construction industry and to create awareness about the profession.
2. To define Boundaries of Responsibilities of Structural Engineer, commensurate with remuneration.
3. To get easy registration with Governments, Corporations and similar organisations all over India, for our members.
4. To reformulate Certification policies adopted by various authorities, to remove anomalies.
5. To convince all Govt. & Semi Govt. bodies for directly engaging Structural Engineer for his services.
6. To disseminate information in various fields of Structural Engineering, to all members.

FIELDS CONSIDERED AS ASPECTS OF STRUCTURAL ENGINEERING

- | | |
|-------------------------------------|--|
| * Structural Designing & Detailing | * Construction Technology & Management |
| * Computer Software | * Geo-Tech & Foundation Engineering |
| * Materials Technology, Ferrocement | * Environmental Engineering |
| * Teaching, Research & Development | * Non Destructive Testing |
| * Rehabilitation of Structures | * Bridge Engineering |
| | & Other related branches |

Rajan Kataria, Haroon Shaikh and V. V. Nori




Fig-2 Typical section at piers

horizontal alignment is mostly straight. The lowest radius of curve of the alignment is 900 m. The ground is reasonably level. The alignment crosses six major roads one major drain and an oil pipe corridor. The soil investigation revealed that open foundations located at about 2.0 m below ground level could be adopted. The main consideration for span configuration was the clearance required for road crossings and bearing in mind that open foundation have to be used.

Choice of basic spans

After studying several alternatives it became clear that with open foundations the span would be in the region of 15 m. Initially, the option of simply supported span of 15 m with neoprene bearings and seismic restrainers was studied. This solution was indeed simple to design and to construct. The cost reduction obtained in this case when compared to elevated viaducts constructed by DMRC was largely due to open foundation and smaller spans. However, there would be a number

of expansion joints and bearings as compared to the elevated viaducts constructed by DMRC. These joints and bearings would certainly pose problems in maintenance and possible replacements. Further, from seismic design considerations, simply-supported structure may not be desirable in the sense that spans tend to dislodge at times.

Proposed span arrangement and integral form of construction

After studying a number of alternatives, a 61-m module with span configuration of 13.5m + 16.5m + 16.5m + 13.5 m appeared to be the best choice. This configuration met with the requirements road crossings and could be used typically for the entire length so as to obtain maximum repetition. Typical cross-section details are shown in Fig 1 and 2. However, different span configurations would be required in the vicinity of the station

buildings and at other locations near the Palam drain crossing and oil pipe corridor crossings. Severe restrictions at the oil pipe corridor crossing and Palam drain crossing called for much larger spans in the range of 36 m.

The height of the rail varied between 7.0 m to 9.0 m above ground level. At a few locations the rail level was 10.30 m above ground level.

Features of typical span configuration

The deck cross section consists of two 1.2-m deep voided girders with a span arrangement of 13.5 m + 16.5 m + 16.5 m + 13.5 m, Fig 1. The deck frames were merged monolithically in to the circular piers of 750 mm diameter for end span 900 mm diameter for intermediate supports. Diaphragms at pier locations are cast-in-situ providing frame action both in transverse and longitudinal directions. The continuity of the structure over intermediate supports in the longitudinal direction is achieved by introducing prestressing cap cables at these locations. In the transverse direction the individual deck slabs get connected by overlapping reinforcement and a cast-in-situ connection. Typical structural model for longitudinal and transverse analysis is shown in Fig 3. For

longitudinal analysis, model was prepared using line elements whereas for transverse analysis FEM model was prepared.

At some locations a span arrangement of four spans of 13.5 m had to be used to suit the site conditions. Reduction in the middle two spans for this configuration did not result in a reduction in the total cost per unit length. A typical configuration of 61 m therefore appeared to be an ideal choice.

The deck slab was required to support an evacuation walkway, parapet and duct loads. The deck slab was additionally required to support concentrated over head electrical (OHE) mast loads which can occur any where along the span.

The precast parapets were designed on a module of 2.7 m. Two diaphragms are provided at 1.35 m on centres. The OHE mast connection load get distributed between two diaphragms, thus providing a better dispersion of concentrated loads on the deck slab.

The deck slab was also designed for axle loads that occur at cross overs. Beyond the last station the track centres had to be gradually increased to 4.725 m to accommodate scissors crossing. This could be accommodated by increasing the width of the cast-in-situ longitudinal connection between the two girders. The same precast deck girder could be used without any changes for the entire stretch.

The substructure consists of open foundations comprising conventional isolated footings resting on medium sand. Corbels are provided for individual circular piers so that precast girders could directly rest on the corbels without any additional temporary supports.

Some of the issues specific to integral form of construction are briefly described below.

- i) *Change in the structural system:* The girders are simply supported when placed on piers. These are rendered continuous by cast-in-situ diaphragms and continuity cables. Effects of creep result in introduction of support moments into the structure. These have been evaluated as per the guidelines

provided in “FIP recommendation - Practical design of structural concrete”.

- ii) *Modulus of elasticity:* For evaluating long-term effects due to creep, shrinkage, uniform rise / fall, foundation settlement, the modulus of elasticity of concrete is reduced by 50 percent. For all other loads such as tractive / braking, centrifugal, earthquake forces normal value of modulus of elasticity is used. The strata being predominantly sandy it is reasonable to expect that foundation settlement due to dead loads (excluding parapets and cast-in-situ concrete for transverse connection) would have already taken place at the time of introduction of continuity by stressing prestressing cables.




Fig. 3 Typical Structural model for longitudinal & transverse analysis

- iii) *Effects of rail-structure interaction:* Another problem specific to ballastless structures is the interaction between the structure and the long welded rails which are connected to the deck with the help of Vossloh 336 fastening system with standard SKL 12 clamp. Effect of rail-structure interaction on simply supported structures with bearings is to introduce forces on piers due to temperature, creep and shrinkage which would otherwise have got dissipated in case of equal spans. In case of integral form of construction the piers are already subjected to forces due to creep, shrinkage, temperature effects. The effect of rail-structure interaction is generally favourable for those components of movements that occur after the rails are installed.



Fig. 4 (a) Platform in Position for II stage Blister Stressing



Fig. 4 (b) A view of II stage Stressing Blisters



Fig. 5 (a) Precast Girder being Lowered



Fig. 5 (b) Box Girders Launched along the Curve Section

Construction methodology

The proposed method of construction was developed by the contractors. The girders are cast within the 30 m strip, erected in position using a gantry straddling across the viaduct, *Fig 5*. The moulds are then shifted to the next module.

Cast-in-situ span

At two locations, namely, oil pipe corridor crossing and Palam drain crossing, spans in the region of 36 m were required. At both these locations cast-in-situ deck construction was adopted. The structures are founded on 1.2 m diameter cast-in-situ bored piles. The piers are integral with the deck structure.




Fig 6 Typical cross section of cast-in-situ span



Fig. 7 Palam Drain Crossing

For cast-insitu spans, adoption of I-girders/box girders would have increased the height of rail above the soffit. At Palam drain crossing the elevated viaduct also crosses an existing bridge which determines the height of the rail. I-girder/box girder type solution would have meant raising the rail height of adjoining standard spans also.

The cross section adopted was derived by integrating the evacuation walkway into the structure, *Fig 6*. The rail height above the soffit remain undisturbed. Palam drain crossing has two spans each of 36 m supported on a central circular pier. *Fig 7*. The pier location was such that it was in line with one of the skew piers supporting the existing road bridge crossing Palam drain. Oil pipe corridor crossing has a single span of 38 m. Cast-in-situ construction required special connection details so that prestressing forces are not transmitted to the piers. This was achieved by supporting the structure on neoprene bearing so that elastic shortening of the girder is not restrained by the monolithic connection with the pier. After completion of prestressing operations concrete is placed in joint with protruding reinforcement for achieving monolithic connection. *Fig. 8* shows another view of the elevated viaduct under construction.



Fig. 8 Elevated Viaduct under construction



Oil Pipe Corridor

Conclusion

The entire 6.47-km long stretch of viaduct is free of bearings. Expansion joints are at 61 m typically; spacings were reduced in a few locations to suit the road /drain crossings station intersection etc. Engineering effort in the design of integral form of construction is substantial more than what would be required for traditional structures with simply supported spans resting on bearings. Integral form of construction does seem to permit cost reduction of the elevated viaducts. It is anticipated that integral form of structures will require much less maintenance efforts and are expected to perform better during earthquakes due to added redundancy.

Acknowledgments

Authors gratefully acknowledge encouragement given by Mr E Sreedharan, Chairman and Managing Director DMRC, Mr. C B K Rao, Director Projects, DMRC and Mr. Shirish B Patel, Chairman Emeritus SPA. Afcons Infrastructure Ltd. are the contractors of this elevated viaduct.

Reference

1. The Indian concrete Journal, September 2005.


Authors :



Mr. Rajan Kataria
Chief Engineer, Design DMRC



Mr Haroon Shaikhis,
Design Engineer. SPA CPL



Dr. V. V. Nori
Chairman of Shirish Patel &
Associates Consultants Pvt. Ltd.
Mumbai

JACK-UP PLATFORMS FOR MARINE WORKS

A B Karnik

Most of the Engineers must be aware of existence of Sagar Samrat used for several years in India as a Key Platform for serving Oil Wells. It is a Versatile Giant Jack-up Platform usable in deep sea operations in Indian Waters. Author of this article has designed several Mini Jack-up Platforms for Marine Works close to Shore. Piling Gantries for Approach and Jetty Head Piles Construction, particularly starting from shore, have also been designed by the Author. For Ship Berthing, Approach Jetty extends in length upto Jetty Head where enough draft (depth) of water is available for Ship Berthing for floatation. Requirement of Jack-up Platform arises out of necessity for construction of piles and allied works away from shore for Mooring Dolphins and Berthing Dolphins away from Main Jetty. Berthing Dolphins resist impact of Ship Berthing. Mooring Dolphins facilitate pulling of Ship to butt against Jetty Head. All these structures are finally interconnected by Structural Steel Walkways for day to day communications.

The article hereafter details three typical Jack-up Platforms designed by the Author for different requirements.

(1) Jack-up Platform at Mormugao Harbour in Goa was used in 1994 for construction of Mooring Dolphin requiring 24 no. 1200 dia. piles. Working Platform size provided was 13.50 m x 9.00 m in plan. Buoyancy Tanks provided were 4 no. 5 m x 2.50 m x 2 m plus 2 no. 1.20 m dia. x 13 m long plus 2 no. 1.20 m dia. x 10.20 m long plus 3 no. 0.80 m dia. x 12 m long. 3 no. 1200 dia. Piles could be completed in one setting of Jack-up. It cannot be pitched accurately in required position. Overhead adjustable arrangement is made for placing piling pulleys in correct position. These arrangements can be clearly seen in the photograph. It is important to note that four spuds provided in four corners are lowered onto the bed and whole platform is raised by about 1 m and locked with spuds. Stationary Platform is thus available to get

accurate location of piles. Sample calculations for Stability of Jack-up in floating mode are given herewith.

(2) Another Jack-up Platform was used at Dahanu in Maharashtra for Ash Disposal Pipe Line Bridge. Structural Steel Bridge with few spans of 30 m each for Pipe Line and Jeepable Road was designed by the Author. Supporting Pier Column had 3 no. piles 600 mm dia. 1.50 m apart forming equilateral triangle. Jack-up Platform was provided with Moving Frame with piling winch etc. mounted on it to align for X co-ordinate of piles and movable suspended piling pulley to align for Y co-ordinate of piles. With these provisions, Jack-up pitched near pier location could complete three piles accurately in desired location. Buoyancy Tanks provided were 2 no. 8 m x 4 m x 2 m deep with clear distance between them of 3 m. Spuds provided at four corners lowered and platform raised and locked onto them as before.

(3) One more Jack-up Platform illustrated here was for Soil Exploration near Jageshwar close to Dahej Port in Gujarat. This is in Narmada River merging into Sea. Water current 3 to 4 m per sec. Plan size of Jack-up out / out was 15 m x 15 m with open space in the centre of 7 m x 7 m. Buoyancy Tanks were 2.5 m deep. Central open space was used for handling equipment for soil exploration. Platform was steadied as before by raising platform on spuds. Spuds provided for this soil exploration were pretty long to cater for larger depths.

Author :




Er. A B Karnik, A senior Consulting Engineer with more than 50 years of experience.
E-mail : arunodaya22@gmail.com




1000 Jack Up Floating



Plan of Jack Up Platform



Views of Jack up platforms



OUTSTANDING STRUCTURAL ENGINEER ISAMBARD KINGDOM BRUNEL

- Dr. B N Kale

It is an attempt to highlight the splendid works of Er. Isambard Kingdom Brunel, a Civil Engineer of the Victorian age.

During a span of just fifty three years, he could build unparall structures, standing erect even today, after over one hundred fifty years.

Those were the days when all works related to construction were done by an engineer. He would design, undertake every work related to construction including supervision, architectural, structural, civil work were done by one person, called 'Engineer'. Apart from this an engineer should have innovative ideas and calibre to complete the work satisfactorily. Brunel was possessing all these professional qualities. Even after such a long time, all the projects of Brunel, enumerated below, are still in nation's service.

Brunel is remembered for variety of bridges, gigantic ships, railways, and tunnels.

His father Marc, also an engineer, migrated to England from France, before his marriage with Sophia. Marc sent Isambard to France for education when he was fourteen years of age. After finishing his basic education and apprenticeship, Brunel returned to England. He was just nineteen years then and his father Marc was executing the job of Thames tunnel. This job was indeed hazardous. To construct a tunnel under ever-flowing Thames river was the first job Brunel was entrusted with. This work was twice suspended earlier, as the water rushed into the

excavated area.

Brunel also failed twice while the work was in progress due to water logging. He was also seriously injured and had to take rest for six months. At last, this half-completed tunnel was rendered serviceable. It is now being used for underground railway, though its name is 'overground'. This is a very wide and sturdy tunnel as could be seen from both the ends.

Brunel is best remembered for bridges and gigantic ships. Clifton suspension bridge near Bristol, the widest and flattest Maidenhead bridge constructed with the help of bricks, on the Thames, having its one pillar in the midst of the riverbed, Hanwell bridge also of bricks, Royal Albert Bridge - oval shaped iron bridge, Bowstring bridge near Bath island - one of the oldest Bridges, to quote a few. Except Clifton suspension bridge, all other bridges have been constructed for railways.

For Great Western Railway, one of the longest railways, Brunel's contribution is by far the greatest. It is only he who could complete the railway's work against all sorts of opposition. He had to convince even the members of the Parliament, the importance of railways. Paddington station, the terminus of the GWR, has



been his creation from first to last. Brunel's statue has been erected on the platform to commemorate his contribution. On many locomotives "ISAMBARD KINGDOM BRUNEL" is conspicuously written.

Suspension bridge at Clifton is indeed a marvellous job. It is about 700 feet long, 80 feet wide and 250 feet over the riverbed. This bridge was constructed mainly for pedestrians and light carts' traffic. Motor cars, automobiles and other speedy vehicles had not been invented till then. The same bridge is able to sustain the pressure of today's speedy vehicular traffic, which speaks a lot about Brunel's engineering skills as well as his foresight. No one would have imagined of such a fast development in vehicular traffic, 150 years ago.

Great Western Ship, Great Britain Ship, and the Great Eastern Ship have been his creations, in the ascending order. All these achievements rightfully bear the word 'GREAT'. The passenger capacity of Great Eastern Ship was over 3500, four times that of a railway. Out of these three, only one, Great Britain Ship, is existing now and has been converted into a museum. It is now an attraction for tourists and students, as well. Over one lakh fifty thousand visitors pay visit to this Ship in a year. The Ship has been honoured with four awards in 2008 for his achievement.

Crimea War was thrust upon England by Russia. Britishers were caught unaware. War means casualties and wounded soldiers. To nurse them, Florence Nightingel rushed to the battle field. The first thing she observed was lack of

sanitation and hospital facilities. Barracks converted temporarily into hospitals could not deliver the goals.

Brunel undertook this job of creation of a makeshift hospital i.e. folding canvas tents and did it in record time. Florence Nightingel had a word of praise for Brunel. His innovative ideas paved way for creating such hospitals for army and during emergency in subsequent years.

After his untimely death, Brunel was honoured with many prestigious awards. In 2002 BBC conducted a survey to find out 100 Great Britons who are respected most. First rank was snatched rightfully by Sir Winston Churchill while the second one was taken away by Brunel. After his name, Shakespeare, Newton etc. were placed in that list. The government as well as private bodies honoured Brunel by issuing a series of postal tickets, two coins and many other ways.

On seeing the list of honours showered on Brunel, one feels happy that the hero did not go 'unsung'. But one wonders how was it possible for Brunel to complete so many important projects in such a small span of life. Nation is built by such dedicated engineers whose life and work show the next generation, the path to tread.

Brunel passed away on 15th September, and Bharat Ratna Mokshagoondam Vishweshwarayya born on the same date is indeed a coincidence. Year is of course different.

Britishers honour this "builder of their nation".

I hope the outstanding work of Brunel will go a long way to inspire the future generations of Civil Engineers.

Career Graph of Brunel



Birth : 9th April 1806
Death : 15th September 1859
Place of Birth : Portsmouth England
Profession : Civil Engineer & Structural Engineer
Parents : Sir Marc Isambard Brunel
Sophia Kingdom
Education : Lycee Henri IV
University Of Caen

Significant Projects :

- ❑ **Bridges** :
 - Clifton Suspension Bridge - one of the biggest bridges
 - Maidenhead Railway Bridge - the flattest & the widest brick arch Bridge
 - Hanwell Bridge
 - Royal Albert Bridge - Oval shape

- Bath Bowstring Bridge - one of the oldest iron bridges

- ❑ **Ships** :
 - Great Western Ship
 - Great Britain Ship
 - Great Eastern Ship - the biggest ship of the time.
- ❑ **Tunnels** :
 - Thames Tunnel
 - Box tunnel - over two miles long one of the longest of the time.
- ❑ **Railway** : Great Western Railway - the longest of the time.
- ❑ **Hospital** : Pre-fabricated Hospital for Crimea War

Acknowledgement :

The article is based on recently published Marathi book "Asa Hota Brunel" by Dnyanesh Prakashan, Nagpur.

Author



Dr. B. N. Kale

The author is a doctorate in Economics. During his visit to United Kingdom, he was fascinated by the works of Brunel. He visited various sites in U.K. and gathered information which has been compiled in his book - "Asa Hota Brunel".


Tel. : 0712-2227479 Mob : 9823366609




(1) Tunnel under Themes - One Side




(2) Tunnel under the Themes river - used by Over ground railways.




(3) Bath Tinnel




(4) Work in progress of the Themes tunnel




(5) BATH Tunnel - used by Railways.
One of the longest tunnel of the Time.



(6) The Royal Albert Bridge - OVEL BRIDGE



(7) Clifton Suspension Bridge - Other side



(8) Clifton Suspension Bridge - Over Avon River - View on one side



(9) Clifton Suspension Bridge - Full view



(10) Maidenhead bridge - Flattest and Widest Brick Arch Bridge.



(11) Royal Albert Bridge - Work in progress



(12) Paddington Station of GWR



(13) Full view of the Clifton Suspension Bridge



(14) The Grand Western Ship - Presently museum.
The only ship in existence.



(15) Propeller of the ship.



(16) Great Western Railway



(17) Fastest Train



(18) Isambard Kingdom Brunel inscribed on
many locomotives to cherish his memory.

INBUILT FERROCEMENT STRUCTURAL FORMWORK

J A Desai

Reinforced cement concrete requires formwork of certain dimensions and shapes to contain concrete at the time of construction for foundations, columns, beams, slabs of buildings and other structures such as bridges, water towers and many others. It is a very important feature right from the time Portland cement was invented because cement requires certain time to gain strength. RCC cannot be thought of, without shuttering. The time factor to provide shuttering and removing the same is significant for time bound BOT projects. Certain time has to be allowed for concrete to acquire design strength. The cost of providing shuttering, blockage of shuttering till concrete gains strength and deshuttering and time consumed is significant aspect of RCC construction. It is generally thought how it can be reduced. Various methods, materials, designs are thought of and adopted to achieve this.

In-built FERROCEMENT STRUCTURAL FORMWORK has been developed to cut down the cost, time required to manufacture, erection, left in position till concrete has gained required strength and deshuttering for casting of column, beams, slabs. All the same the time of shuttering shall be reduced and activity of deshuttering shall be eliminated totally. Similarly for any structures such as bridges, irrigation structures, water towers, jetties and many other structures. Ferrocement shuttering for slabs and beams is manufactured on machinery set-up under controlled conditions as plates, beams in the shape of 'U' and columns as box. The reinforcement required for columns, beams, slabs shall be incorporated in the shuttering itself. The activities of reinforcement, cutting, bending placing at site shall be eliminated totally and shifted to manufacturing area. Some reinforcement if necessary can be added at site.

The units are cast in parts or in full length depending upon the method of installation of shuttering. If the shuttering is to be installed by manual handling, then the shuttering shall be cast in units possible to be handled by 5 – 6 persons assembled at site for full size of slabs and beams and columns. If mechanical method of installation of shuttering is adopted the full size shuttering units can be manufactured, erected and installed in position.

After Ferrocement shuttering is placed in position, necessary connection with adjacent members are made mainly by welding, wiremesh lapping and cement matrix application. If necessary additional reinforcement is placed. The concrete at the joints, beams, columns is finished in line level and surface configuration as per requirement. After this plain cement concrete of required strength is poured in the hollow of relevant members.

The system is ready to take up next further work. The work can be strong enough for taking up the



Elaborate steel formwork as above is totally eliminated.



Concrete surface as seen above shall be surface of Inbuilt Ferro-cement Structural Formwork.

Inbuilt Ferrocement Structural Formwork

- Thin section Formwork for slabs, beams, columns
- Manufactured on machinery set-up
- Reinforcement of slabs, beams, columns incorporated in Formwork body
- If required, additional reinforcement can be provided
- Time saving by about 10-15% and Cost saving about 10%
- The wiremesh in the formwork makes the structures strong with no/negligible requirement for repairs and retrofitting in the life of the structure
- It makes the structure best earthquake and cyclone resistant with least damages
- The structure shakes like jelly and comes to its original position after Earthquake and cyclone is gone.
- The structure shall not require repairs almost for life time.
- The structure shall resist fire upto 75°C for 48 hours temperature and duration can be increased

Ferrocement High Rise Buildings

- reduce cost by about 10% of R.C.C.
- reduce time of construction by about 10% of R.C.C.
- eliminates formwork of columns, beams, slabs
- environment friendly
- inbuilt structural formwork
- is more durable, water-proof than R.C.C.
- do not require major repairs in its life time
- remain almost intact during earthquake and cyclone
- can swing by a metre or so with no damage
- resist fire for almost 48 hours 750°C and can be made to resist higher temperatures.
- has less self-weight by about 50% of R.C.C.

construction of the next floor after 2-3 days. Similarly works on the floor below such as walls, doors, windows flooring can be taken up. There will be no props to create hindrances.

Our method of in-built ferrocement shuttering has many advantages from the point of time convenience cost and strength and time as below:-

There will be saving in time for installation of shuttering for beams, columns, slabs as compared to the time for wooden or steel shuttering and provision of props. Since the re-inforcement of beams, columns, slabs shall be within the body of ferrocement shuttering mass, the pouring of concrete and vibration or self-leveling concrete shall be very much easy and fast.



All the props and Wooden Formwork shall be eliminated by Inbuilt Ferrocement Structural formwork.

- Cost of shuttering is eliminated. Some additional reinforcement, if required, is placed within the hollow of shuttering. The next below and floor above can be taken up after two-three days.


- Cement matrix of Ferrocement shuttering will be structural integrated with the concrete of slabs, beams, columns. To that extent concrete for the member is saved. There shall be saving in concrete by approx. 10 – 15%.

- In addition to the normal strength of the structures, the skin strength will enhance the strength to a large extent.

- The time element of de-shuttering is eliminated totally and the area below is ready for other items of works such as wall, doors, window, floors, to be taken up. Similarly further work at next floor can be taken up soon.

- The surface of shuttering shall have wiremesh reinforcement which will make structure durable, strong waterproof and crack resistant. Repairs required in concrete after some years shall be eliminated for almost life of the structure. Thus performance of the structure shall be most efficient.

- The structure is most durable, fire resistant upto 750°C, waterproof, better earthquake resistant



Structural ferrocement Formwork used for portals, beams, columns for above representative structures.

and can be guaranteed.

- The FINANCE employed to execute the project shall start giving returns early. This is most important for BOT Projects.

- CONSTRUCTION OF BRIDGE, WALKWAYS, piers and beams and decks will cause least DISTURBANCE to road and pedestrian traffic. All aspects of wood and steel shuttering at site are ELIMINATED. Construction TIME AND SPACE occupied on road will reduce.

The RCC structures constructed with Inbuilt Structural Ferrocement Formwork shall get damaged the least and resist effectively all types of disasters such as earthquake, cyclones, fires and floods. The structures may get deformed but shall not collapse. This phenomena shall prevent loss of life because the people trapped can conveniently come out of such structures. Such contribution of RCC building with Inbuilt Structural Formwork shall be most invaluable. Such structures can be repaired and restored with least expenditure. Thus there will be considerable saving in prevention of loss of property.

The most important and significant contribution of inbuilt Ferrocement structural formwork is that it saves lakhs of square meters of wood, plywood and steel formwork. Thus this system is most environment friendly.

Author :



Mr. J A Desai is a consultant for Ferro cement applications.
E-mail : jadfc@yahoo.com

COST EFFECTIVE SOFTWARES IN ENGINEERING

ENHANCE PRODUCTIVITY : REDUCE MAN-HOURS : SAVE COSTS

SUPER CIVIL CD

80 nos of Design Programs + 400 MB of Power Packed Info + Productivity Tools. Cost : Rs 1500

S S F

Analysis, Design, Costing & Drawing of Structural Steel Floors. Cost : Rs 3000

Q T Y

Quantity, Cost Estimation & Project Planning of Buildings. Cost : Rs 1800

R O A D S

52 nos of Design Programs & Rate Analysis of 498 # of Road Items as per IRC. Cost : Rs 2200

SUPER REAL VALUATION

54 nos. of Programs for Valuation of Immovable Properties. Cost : Rs 2000

STEEL 2007

Limit State Design of Steel Members as per IS 800 : 2007 Cost : Rs 2000

R C F

Analysis, Design, Costing and Drawing of Multi-Storey RC Buildings. Cost : Rs 3000

2D FRAME ANALYSIS

Discover the Joy of Structural Analysis of Multi-Storey Portals & Frames. Cost : Rs 1500

SUPER RATE ANALYSIS

Rate Analysis of 1294 Building Items and CPWD Specs. Cost : Rs 2000

ROAD ESTIMATE

QTY, Costing, Project Planning & Area/Volume Calc. of Roads, L & X Sec. in ACAD. Cost : Rs 2200

R A F T

Analysis, Design, Costing and Drawing of RC Raft Foundations. Cost : Rs 3000

SITE CONTROL

A Database Management Software for Resource Control at Site. Cost : Rs 2000

Demand Draft favoring Mr. Y. A. Agboatwala may be sent to: 1802, Jamuna Amrut, 219, Patel Estate, S. V. Road, Jogeshwari (W), Mumbai 400102. URL: www.supercivilcd.com Email: yaa@supercivilcd.com Tel : 022 - 26783525, Cell : 9820792254

Missing You !

We appeal to all ISSE members to provide their Name, membership number, correct address , contact number and email to ISSE. We notice that around 125 journals were returned by courier due to incorrect address. Please intimate ISSE about your change of address and e-mail on issemumbai@gmail.com

ISSE Journals sent to following members were returned. Please provide your correct address-

M -2- Raghubir Kumar Sharma	M-371- Vashudev Deshpande
M- 52 - Promod Ramani	M-379- Gururaj Narshinha Joshi
M- 55 - M.S. Venkatesh	M- 380- Shrinivas Tukaram Badave
M- 58- Murlidhar.L.Bhirud	M-383- Laxman Ganesh samudra
M-73- Jitendra.A.Bhandwalkar	M-391- Shekhar Chakravarti Ghatte
M-79- R.J.Limani	M-455- Mahua Ajay Chakarabarti
M-83- Arup. K. Sarbadhikary	M-461- Kedar Vasant Phadnis
M-87- Ravish Abdul Reheman Dhuru	M-463- Kailas Niwritirao Zalte
M-93- Varanasi Srinivasa Rao	M-470- Shijil Medelath Balchandran
M-108- Khurd Mahadev Udhav	M-473- Kaivant Champakla Shah
M-116- Gundo Ganpat Lakule	M-481- Delip Madhukar Wani
M- 129- Virendra Kumar Jain	M-505- Shashikant Sahardchandra Thatte
M-135- Suresh M Aiyar	M-509- Rajesh Ramchandra Patil
M-137-Jera K Bhalodia	M-512- Anupama Jayant Kanbur
M-142- Abhay Dinkar Patil	M-516- Devendra Kumar Upadhyay
M-150- Rajkumar H Rathi	M-520- Kedar Dilip Moghe
M-152- Harshad V Chavan	M-547- Narayan Ghorakh Gore
M-153-Sanjay B Kamdar	M-593- Balkrishana Suresh Chandar
M-155- Akshay H Kahojkar	M-603- Minal Rajesh Phadnis
M-165- Sarosh N Khot	M-612- R.K.Padwal
M-186- Abhimanyu Londhe	M-626- Ravindra Ashok Karnawat
M-187- Anilkumar Anandji Pithwa	M-643- Vithal Raghunath Damle
M-188- Harish Harendraprasad Joshi	M-647- Mohd. Shafique Momin
M-197- Gutam Jainarayan	M-648- Jalauddin Ansari
M-205- Venkata Naga Prabhakara Rao Vedula	M-650- Ashok Girdhar Patel
M-208- ketan Belsara	M-652-Dilp Ismail Londhe
M-227- Prakash Shripal Kudche	M-657- Kaushal Kishor
M-228- Manjal Anand Kantilal	M-666- Shubhashini Shrikant Naik
M-232- Ravishankar Pandurang Shinde	M-673- R.Pragasam
M-235- Kalidas Bhudas Jiddewar	M-683- Pravin Sudhakar Mulay
M-236- Sanjeev Ramesh Raje	M-694- Prashant Vinayak Lele
M-237- Randhir Shashikant Rane	M-705- Kavita Amarnath Kulkarni
M-239- Promod Nivrutti Jagadhane	M-706- Sandeep Shankar Shirsagar
M-242- Joytiyoti Bhattacharjee	M-726- Rahul Ramakant Kulkarni
M-244- Japrakash Manohar Ranadive	M-733- Yogesh Govind Bhang
M-252- Devendra S.Shah	M-737- Madhav Dattatraya Tambekar
M-257- Sureshkumar Shankarlal Oswal	M-747- Suresh Vishwanath Ramadurgakar
M-260- Bhalchandra Anandrao Gangurde	M-749- Amin Abdulaziz Sheikh
M-261- Santosh R.Navale	M-754- Juzer Anmedali Tinwala
M-262- Pravin Madhukar Kide	M-768- Divayankant Vaikunthbhai Panchchigar
M-265- Dattatraya Krishana Kanhare	M-772- M.V.Jayram
M-269- Shrikant Vishnu Jadhav	M-773- Sadashiv Madev Bhagvat
M-274- Sanjeev Shriram Solanki	M-774- Deepak Dinanath Naik
M-281- Amab Chakraborty	M-794- Anilkumar Hari Bimbikar
M-287- Ashfaq Ahmed Iqbal Ahmeb Ansari	M-825- Anil Anant Dharulkar
M-288- Jalis Sharaf Phegari	M-867- Satish Vanilal Kansara
M-289- Fairoz Karim Sheikh	M-884-Maruti Jambagi
M-295 Vishwajit P Pawar	M-921- Sachin Kumaran Cherayerumal
M-296- Jayant Dattatraya Banat	O-6- Span Consultants Pvt.Ltd
M-302- Nilesh Narendra Vyas	P-6- Jigna Development Construction Pvt .Ltd
M-304-Vinesh Rameshchandra Pandya	P-8- Indage Development Construction Pvt.Ltd
M-322-Arvind Babulal shah	P-10_ M/S Buildarch
M-336- Sanjeevkumar Pyarelal Yadav	P-16- Mehra
M-338- Arun Govind Apte	P-19- Mane
M-349- Jatan Arun Bhiuta	P-28-Chaitanya Enterprises
M-358- Sunil Gundopant Mutalik	

Publications available at ISSE head office

Title	Donation amount Rs.
Publications :	
• Design of Reinforced Concrete Structures for Earthquake Resistance	800
• Professional Services by Structural Design Consultant - Manual for Practice	200
Proceedings :	
• National Conference on Corrosion Controlled Structure in New Millenium	400
• Workshop on ISO-9001 for Construction Industry	200
• Brain Storming Session on Use of Speciality Products in Structures	250
• Workshop on Software Tools for Structural Design of Buildings with CD	550
• Workshop on Structural Audit	200
• Workshop on-Seismic Design of Building	200
• Workshop on Effective Use of Structural Software.	200
• Workshop on Effective Use of Structural Software - CD	150
• Workshop on Shear Walls in Highrise Buildings	200
• Seminar on Innovative Repair Materials / Chemicals	250
• Seminar on Foundations for Highrise Buildings	200
• Seminar on Structural Detailing in RCC Buildings	250
• Workshop on Pile Foundations	200
• Seminar on Pre-engineered Structures	200

BE AN ISSE AUTHOR

Articles and technical papers are the heart of a technical journal. We invite you to write technical articles and papers for publication in the ISSE Journal. You may write about:

- An innovative concept or approach
- Proposed theoretical, computational or practical improvement on an existing concept
- An experimental study
- Guidelines and standards developed
- Compilation of rare/scattered information on the latest technological advances
- A case study: Challenges in design and construction
- Your viewpoint on current professional practices

While submitting your article for publication, please follow the guidelines given below:

- Page size: A4, Top, Bottom, Left and Right margins: 1", Font: Arial, 10 pt
- Max length of article: 5 pages including tables and figures
- The manuscript should contain the title of article and names, qualifications, designations, addresses and email addresses of the authors along with photograph.
- The matter should be relevant to the subject and should be organized in a logical flow. It may be divided into sections and sub-sections, if necessary.
- While, sketches and drawings should preferably be in Corel-draw, other appropriate formats are also acceptable. Photographs should be sharp and clear.
- Figures, photographs and tables should be numbered and should have captions.
- Notations, if used, should be clearly defined.
- Article should be sent by email to issemumbai@gmail.com

Articles may be reviewed and edited before publication.

PRODUCT REVIEW

We have now introduced a new section, "Product Review" into the ISSE journal. This is where manufacturers and dealers can introduce their products such as construction materials, chemicals, equipment, software etc, through a technical review. Only one product review may be printed in each issue. A space of up to two pages of the journal may be allocated to this feature.

The main purpose of this feature is to introduce the newer products available in the market to our readers, and therefore, the review should be technically intensive. The manufacturers and dealers can highlight the advantages and uniqueness of the featured products in the review.

The review should cover one or two products only and may include their technical specifications, method of installation/application, available product range, unique features, advantage, photographs etc. It should not be a direct commercial promotion of the products. However, the contributor may include his contact details at the end of the review. Matter received may be suitably edited and modified in consultation with the contributor.

For details please call the editor.

ADVERTISEMENT TARIFF IN ISSE JOURNAL

E-mail : issemumbai@gmail.com

ISSE Journal	Advertise Size mm	Tariff per insertion
Back cover page (Colour)	170 x 240	Rs. 15,000/-
Inside front cover page (Colour)	170 x 240	Rs. 12,000/-
Inside back cover page (Colour)	170 x 240	Rs. 12,000/-
Inner colour page	170 x 240	Rs. 10,000/-
Inner B/W full page	190 x 240	Rs. 6,000/-
Inner B/W half page	190 x 120	Rs. 3,000/-

Note : 10% discount is offered for advance booking of colour advertisement for 4 issues, provided entire payment is made in advance

APPEAL TO ISSE MEMBERS

We appeal to ISSE members to actively participate in all functions and activities of ISSE.

Member can suggest new topics for discussion during the seminars and workshops, contribute in arranging expert lectures on various civil engineering subjects.

Senior members can share their knowledge and experience through short evening lectures.

We are looking for participation from Engineering Colleges through their faculty and students. Civil Engineering Department can send the interesting projects done by undergraduate and post-graduate students in the form of articles which can be published in our Journal.

Edited and published by N K Bhattacharyya for ISSE, C/o S G Dharmadhikari, 24 Pandit Niwas, 3rd floor S K Bole Marg, Dadar (W), Mumbai 400 028. Tel 91-22-24365240, Fax-91-22-24224096, e-mail issemumbai@gmail.com Web (www.isse.org.in) for private circulation and printed by S L Bengali, Bensan Printers, 15, Pandit Niwas, S K Bole Road, Dadar, Mumbai 400 028

AUTHORISED DISTRIBUTORS FOR
TATA TISCON (TMT, CRS)
SKM Constra
(A Division of SKM Steels Ltd.)



SKM Constra
(A Division of SKM Steels Ltd.)

Distributors for Central Line of Mumbai

Sandhurst Building, 3rd Floor, Opera House,
524, S.V.P. Road, Mumbai - 400 004. INDIA
Tel. : +91 (22) 4343 2000 • Fax : +91 (22) 2386 1782
E-mail : info.constra@skmsteels.com


Reflecta-Range™

Leading the way in protection
against oxidation and corrosion



The product Structure

Eleven layers of
innovative insulation
protected by our
patented coating




The REFLECTA-RANGE™ of Products

- REFLECTA-SHIELD™
- REFLECTA-CELL®
- REFLECTA-GUARD™

Green Insulation™ products are suitable for
Residential • Commercial • Industrial Building applications

✓ Energy Saving ✓ Lasting Comfort ✓ Safe and Green

Authorised Distributor :

 **Roofex**

Suite No.19, 1st Floor,
Plot No. 3A, Udyog Nagar,
Goregaon (W), Mumbai - 400 062.

Tel.: 91-22-2876 6563 / 2876 8881
Fax : 91-22-2876 3244

E-mail : hitesh@roofex.in
Web : www.roofex.co.in